



## Explosion Proof EF24 Transmitter (only) 6 Buttons 2 Speed

### Características Esenciales

- 1 Años de Garantía, Partes y Servicios Disponibles en América

## Especificaciones Técnicas

|                                       |                                           |                                 |                                      |
|---------------------------------------|-------------------------------------------|---------------------------------|--------------------------------------|
| Codigo FCC                            | OFNF21                                    | Rango de Frecuencia             | VHF: 310~331 MHz; UHF: 425 ~ 446 MHz |
| Fuente de Alimentación del Transmisor | 4 AA batteries                            | Parada de Emergencia            | Yes                                  |
| Material                              | Glass-Fiber PA                            | Rango de temperatura de Trabajo | -40 ~ 185 °F / -40 ~ 85°C            |
| Distancia de Control                  | 300 ft up to 600 ft with optional antenna | Normas                          | FCC and OSHA standard 1910.179       |
| Código de Seguridad                   | 32 bits (4.3 billion)                     | Garantía                        | 1 Year                               |
| Potencia del Transmisor               | ≤10dBm                                    |                                 |                                      |

## EF-24 TRANSMITTER

Explosion-proof design



MODEL: EF24-TX  
ITEM CODE: 924-400-001  
Dimension: 186 x 61 x 51 mm  
Weight: 280g (without batteries)



EF24-6S/D

EF24-8S/D

EF24-10S/D

EF24-12S/D

### Product features


- 10 double steps pushbuttons + EMERGENCY STOP + START KEY + SPARE
- 20 control contactors
- Battery voltage warning device, the power supply is cut off during low power
- Safety key switch is to prevent from unauthorized users
- Program the button function by computer interface
- Up/down, east/west, south/north can be programmed to to interlock or non-interlock
- Start key can be programmed to start, toggle switch, normal or other functions
- The spare buttons can be programmed to start, toggle, interlock or normal, etc

### Standard Configuration

- One transmitter (with hanging belt)
- One dust bag
- One receiver
- Receiver is with 1.6 meter cable
- Battery: one pair
- One receive antenna
- Operation and maintenance manual

### Dual power supply:

EF24 is new series explosion-proof radio remote control based on F24 series, strictly complies with explosion-proof criterion GB3638.1 and GB3836.4, and has passed EXiB I BT4 intrinsic safety certification, can operate safely in the chemical and petrochemical industries, mining and other flammable, explosive and hazardous environments,



## Peso & Dimensiones

Peso Total

1 lbs / 1 Kg

Referential Images / Imágenes Referenciales

Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso